



FLATBED TRAILER

Phone (270)-522-1008

Fax (270)-522-1098

QUOTE

ORDER

A Valabesh National Company

QUANTITY:

Quantity input box

Name, Address, State & Zip, Phone, Contact, Date, Terms, Sales Agent, P.O. No., Serial Number, Job/No./Model No., Delivery Date, Ship Via

I BASE TRAILER REFERENCE:

LENGTH, TYPE, WIDTH & FRONT CORNERS. Options: 42', 45', 48', 53', Other. 524, 724, 96" Wide, 102" Wide. Square - Std, 45 Degree. NOTES:

ALUMINUM BULKHEAD. Options: None-Std, Removable, DOT 48" (Includes 10" return, side kit starter angle), Removable, DOT 48" (Includes 22" return, side kit starter angle, side kit bow storage), Permanent, DOT 48" (Straight, No return), Removable, 60" (Includes 10" return, side kit starter angle), Other, 40"Ch / Binder holder, 48"Ch / Binder holder, Steps on bulkhead

FLOOR, SIDE RAIL AND CONCENTRATED LOAD REINFORCEMENT. Options: Smooth Alum-Std, Anti-Skid Alum, Other, Channel Rail-Std, Lock Rite Rail, Pockets 24" O.C. w/ 2 Spools between., Other, 3-Nailers-Std, 2-Nailers, No Nailers, Chain Tie Downs / Pr, Lock Rite Tie Down/Pr, NOTES, Apitong-Std, Trans Deck, Other, 16" Xmbers-Std, 12" Xmbers, 22" Xmbers, Coil Pack (M)-Std, Coil Pack (None), Coil Pack(F,M,R), Coil Pack (Full), Coil Well 12" C/M, Coil Well 16" C/M, Add'l inner stub floor x-members, NOTES

WINCHES. Options: Track "LL" R/S-Std, Track "LL" C/S, Other, None, Length, Winch, sliding, Winch, fixed, Other, 4" x 30' Flat Hook, 4" x 27' Flat Hook, Full Length Hook Bar, Other, NOTES

PRIMARY SUSPENSION. Options: Intraax AANT230-Std, Other, HP Spindle-Std, HN Spindle. PRIMARY SUSPENSION NOTES

PRIMARY SUSPENSION CONTROLS. Options: Manual dump all bags w/ ball valve control D/S, 7-way ISO auxiliary plug w/ 4-wire cable to rear, 4-way auxiliary plug w/ 4-wire cable to rear, Gladhand Disconnect Dump All Bags, Elec. Cntrls for other options-Must describe. ADDITIONAL CONTROL NOTES:

AUXILIARY SUSPENSION. Options: Intraax, Other. AUXILIARY SUSPENSION DESCRIPTION

AUXILIARY SUSPENSION CONTROLS. Options: Air Controls, Electric Controls, Other. ADDITIONAL AUXILIARY CONTROL NOTES

SUSP. SPACING FROM REAR AXLE TO FRONT:

REAR SUSPENSION SETTING. Options: 24" STD for Intraax, Other

HUBS, DRUMS, BRAKES AND MISC. Options: Dura Lite-Std, Aluminum, Steel, CentriFuse-Std, Cast, Other, 16 1/2" x7" Extended Service Lining-Std, Other, 4S/2M-Std, Dust Shields

PAINT. Options: Black, Other, Cam Guards-Std

