



Dependable Efficiency for the Demanding Workday

Tough and sturdy, the Wabash Cargo XL Body featuring DuraPlate Technology is ideal for effortlessly carrying cargo on shorter, multi-delivery routes. With the ability to turn tight corners, the Cargo XL Body is the solution for quicker delivery to just about anywhere.

Features

- DuraPlate sidewalls for extreme durability and damage resistance with increased cubes
- One Piece Header System eliminates corner caps, increasing front wall strength
- Flat floor for maximized cargo space
- Step bumper for easy and safe cargo entry
- V-groove threshold protects rear entry and eases cleaning
- Solutions available for traditional, alternative fuel and electrified chassis








Specifications

WIDTH	LENGTH	HEIGHT		
		79"	85"	91"
86" (Transit only) DRW	12'	•	•	
	14'	•	•	
	15'	•	•	
96" DRW	12'	•	•	
	14'	•	•	
	15'		•	•
	16'		•	•
	17'		•	•

[•] Available sizes limited by chassis type







Translucent roof



Backup camera

Chassis Type	Cutaway	
Truck Body Type	Dry freight	
Sidewalls	6mm DuraPlate white panels	
Front	 FRP Solid bulkhead, setback 4" FRP white front wall One-piece aluminum header Extruded-aluminum radius vertical front corners 	
Rear Frame	 Painted galvannealed steel 14 ga. header 12 ga. corner posts 10 ga. one-piece V-groove threshold Internal gussets 	
Rear Door	Premium roll-up with 6" header Maximum Security (MS) lock	
Floor	18mm hardwood plywood flat floor	
Subframe	 3" formed "C"-channel cross members on 16" C/L High strength 2" channel longsills High strength puck mounted bracket system Pre-coated understructure 	
Roof	One-piece .032" aluminum skin Galvanized-steel anti-snag roof bows on 24" C/L	
Interior Lights	LED dome light with rear switch - hot wired	

Exterior Lights	LED clearance lights LED oval taillights with integrated back-up lights - surface mounted	
Bumper	Pooched step	
Warranty	 1-year white surface and leaks 3-year/36,000-mile limited bulkhead-to-bumper warranty 5-year limited structural warranty (roof, wall and floor structure) See our warranty policy for details 	

Options

Front	Wind fairing Tall cab access door with roof conversion	
Roof	Translucent roof	
Floor	2" x 6" dense pine, 1-1/8" laminated hardwood and inverted T extruded aluminum non-slip floor	
Rear Door	Full opening swing door, 48-1/2" or 60" wide roll-up door	
Side Door	 32" swing door with aluminum step well 30" sliding door with aluminum stepwell 30" or 42" swing side door with stirrup step 	
Cargo Control	Bonded and riveted E-track	
Shelving	Fold-up shelving	
Liftgates	Contact your representative for more information	