

	Spec #1	Spec #2	Spec #3	Spec #4
Length	53' Van	53' Van	53' Van	53' Van
Height	13'6" high	13'6" high	13'6" high	13'6" high
Width	102" wide	102" wide	102" wide	102" wide
Door Opening	Door opening 105.5625	Door opening 105.5625	Door opening 105.5625	Door opening 105.5625
Inside Height	Inside Height @ Front & Rear 104.00"	Inside Height @ Front & Rear 104.00"	Inside Height @ Front & Rear 104.00"	Inside Height @ Front & Rear 104.00"
Wheel End	Tandem w/Tapered spindle & Pro-Torq nut	Tandem w/Tapered spindle & Pro-Torq nut	Tandem w/Tapered spindle & Pro-Torq nut	Tandem w/Tapered spindle & Pro-Torq nut
Suspension	UltraK Air Ride	UltraK Air ride	UltraK Air ride	UltraK Air ride
Tire	Hankook TL 21295/75R22.5	Hankook TL 21295/75R22.5	Hankook TL 21295/75R22.5	Hankook TL 21295/75R22.5
Wheels	Alum Outers/Steel Inners	Alum Outers/Steel Inners	Alum Outers/Steel Inners	Alum Outers/Steel Inners
Mudflaps	Wabash branded, Black 24 x 27 Mudflaps	Wabash branded, Black 24 x 27 Mudflaps	Wabash branded, Black 24 x 27 Mudflaps	Wabash branded, Black 24 x 27 Mudflaps
Landing Gear	Jost A441	Jost A441	Jost A441	Jost A441
Floor Rating	18K rated floor, 12" XM	18K rated floor, 12" XM	18K rated floor, 12" XM	18K rated floor, 12" XM
Cross Members	12" on center Steel I-beam Landing Gear & Slide	12" on center Steel I-beam Landing Gear & Slide	12" on center Steel I-beam Landing Gear & Slide	12" on center Steel I-beam Landing Gear & Slide
Cross Members (bay)	12" on center Alum I-beam Bay	12" on center Alum I-beam Bay	12" on center Alum I-beam Bay	12" on center Alum I-beam Bay
Floor	Flat non skid Alum floor, 1.62" insulation	Flat non skid Alum floor, 1.62" insulation	Duct non skid Alum floor, 2.50" insulation	Duct non skid Alum floor, 2.50" insulation
Threshold	No threshold	No threshold	Threshold 5.25" x 6.76" dock plates across rear	Threshold 5.25" x 6.76" dock plates across rear
Floor Drains	Floor Drains in each corner, No Trough	No Trough	Front & Rear Trough	Front & Rear Trough
Roof	.032 Alum roof/ 2.0 Insulation/24" roof bow spacing	.032 Alum roof/ 2.0 Insulation/24" roof bow spacing	.032 Alum roof/ 3.25" Insulation	.032 Alum roof/ 3.25" Insulation
Front Wall	.050 Alum white front wall/3.5" thick	.050 Alum white front wall/3.5" thick	.050 Alum white front wall/3.5" thick	.050 Alum white front wall/3.5" thick
Sidewall	.040 Smooth white sidewall/2.0 insulation	.040 Corrugated white sidewall/2.0 insulation	.040 Corrugated white sidewall/2.0 insulation	.040 Corrugated white sidewall/2.0 insulation
Posts	Interior alum posts, 16" FLG/24" RLG spacing	Interior alum posts, 16" FLG/24" RLG spacing	Interior alum posts, 16" FLG/24" RLG spacing	Interior alum posts, 16" FLG/24" RLG spacing
Scuff	16" x .160 Composite scuff	16" x .160 composite scuff	16" x .160 composite scuff	16" x .160 composite scuff
Rear Frame	SS rear frame/Galv RIG Bolt-On	SS rear frame/Galv RIG Bolt-On	SS rear frame/Galv RIG Bolt-On	SS rear frame/Galv RIG Bolt-On
Rear Door	Swing Quilted SS rear door/1R 1C Galv lockrod	Swing Quilted SS rear door/1R 1C Galv lockrod	Swing Quilted SS rear door/1R 1C Galv lockrod	Swing Quilted SS rear door/1R 1C Galv lockrod
Bumper	SS dock bumper included	SS dock bumper included	SS dock bumper included	SS dock bumper included
Lighting	All Trucklite LED Lights 5 Rear TL-33 Upper ID's	Trucklite Lights 5 Rear TL-33 Upper ID's	Trucklite Lights 5 Rear TL-33 Upper ID's	Trucklite Lights 5 Rear TL-33 Upper ID's
ABS	Wabco 2S/1M ABS	Wabco 2S/1M ABS	Wabco 2S/1M ABS	Wabco 2S/1M ABS
License Plate	T/L- 97960 Cardholder	T/L- 97960 Cardholder	T/L- 97960 Cardholder	T/L- 97960 Cardholder
E-Track/ Cargo Securement	E-track 1 row full length @ 49" from floor	E-track is available(2 locations only 30" & 60")	E-track 1 row full length @ 49" from floor	E-track is NOT available

Options		
Front/Rear Vents	Transtex TopKit	Tire Inflation
Reefer Steps/Handle	Rubrail	Placards/Cardholders
Side skirts	Rear Step/Grabhandle	Galv/Steel XM's
SS Front wall	Additional Lockrods	Maxx 22T disc brakes IPO drum
Overhead Door	5 lights rear header	Polyurethane bolt on dock bumper IPO SS
Alum Swing Door IPO SSQ		

* Trailers built now through November 30, 2024, are designated as 2025 Model Year. Trailers built from December 1, 2024, to November 30, 2025, will be designated as 2026 Model Year.