

**AIR BRAKE**

# FLATBED TILT

40,000 GVW • 80,000 GVW



**BEHNKE**  
TRAILERS SINCE 1967

**BT**



(563)744-3246

[www.behnkeenterprises.com](http://www.behnkeenterprises.com)

**40,000 lb. GVWR (Tandem Axle)**

Model #	Tilt Length	Stationary	Bed Width
FB8X28TPT-40L	24'	4'	102"
FB8X30TPT-40L	24'	6'	102"
FB8X32TPT-40L	24'	8'	102"
FB8X34TPT-40L	24'	10'	102"
<b>(1) 22,500 lb. Air Brake Axles; Auto Slack Adjust &amp; Park Brake, Non ABS</b>			
<b>(1) 22,500 lb. Air Brake Axles; Auto Slack Adjust &amp; Park Brake, ABS</b>			
<b>(8) ST235-75R-17.5 (18-Ply) Tires on 8-Hole Dual Wheels</b>			

**50,000 lb. GVWR (Triple Axle)**

Model #	Tilt Length	Stationary	Bed Width
FB8X28TPT-50L	24'	4'	102"
FB8X30TPT-50L	24'	6'	102"
FB8X32TPT-50L	24'	8'	102"
FB8X34TPT-50L	24'	10'	102"
<b>(1) 22,500 lb. Air Brake Axles; Auto Slack Adjust &amp; Park Brake, Non ABS</b>			
<b>(2) 22,500 lb. Air Brake Axles; Auto Slack Adjust &amp; Park Brake, ABS</b>			
<b>(12) ST235-75R-17.5 (18-Ply) Tires on 8-Hole Dual Wheels</b>			

Bottom Frame: Manufactured Beam, 80 KSI Web, 100 KSI Flange

Top Frame: 10 x 2 x 1/4 tube, 8" channel side rails

4" Jr. I-Beam Crossmembers on 16" centers

Adjustable Pintle Hitch

(1) V-shaped Tongue Mount Toolbox

(2) Dual Speed Semi-Style Landing Gear

Dual Cushion Cylinders with Air Assist

D-rings every 4' on Side Rail (No stake pockets or rub rail)

Oak floor

(2) 1/2" Grade 70 Safety Chains

Light Plug Holder • Modular Wire Harness

Rubber Mounted LED Lights

Reflector Tape • Mud Flaps

Zinc Rich Primed and Powder Coated

