

40,000 GVW • 50,000 GVW

# AIR TILT FLATBED



*Optional Air Ramps*



**BEHNKE**  
TRAILERS SINCE 1987

[www.behnkeenterprises.com](http://www.behnkeenterprises.com)



(563)744-3246

# AIR TILT FLATBED

40,000 GVW • 50,000 GVW

AIR TILT FLATBED

## 40,000 lb. GVWR (Tandem Axle)

Model #	Bed Length	Beavertail	Bed Width
FB8X31ATPT-40L	24'	7'	102"
<i>(1) 22,500 lb. Heavy Duty Oil Bath Axle w/ Air Brake &amp; Slack Adjust Park Brake</i>			
<i>(1) 22,500 lb. Heavy Duty Oil Bath Axle w/ Air Brake, ABS</i>			
<i>(8) ST235-75R-17.5 (18-Ply) Tires on 8-Hole Dual Wheels</i>			

## 50,000 lb. GVWR (Tri-Axle)

Model #	Bed Length	Beavertail	Bed Width
FB8X31ATPT-50L Tri	24'	7'	102"
<i>(1) 22,500 lb. Heavy Duty Oil Bath Axle w/ Air Brake &amp; Slack Adjust Park Brake</i>			
<i>(2) 22,500 lb. Heavy Duty Oil Bath Axle w/ Air Brake, ABS</i>			
<i>(12) ST235-75R-17.5 (18-Ply) Tires on 8-Hole Dual Wheels</i>			

## 50,000 lb. GVWR (Tri-Axle)

Model #	Bed Length	Beavertail	Bed Width
FB8X31ATPT-50AL Tri	24'	7'	102"
<i>(1) 22,500 lb. Heavy Duty Oil Bath Axle w/ Air Brake &amp; Slack Adjust Park Brake, Air Ride Air Lift</i>			
<i>(2) 22,500 lb. Heavy Duty Oil Bath Axle w/ Air Brake, ABS</i>			
<i>(12) ST235-75R-17.5 (18-Ply) Tires on 8-Hole Dual Wheels</i>			

### Standard Equipment

- 1 Piece I-beam Constuction, 80 ksi web and T1 flanges
- 7' Wood Beavertail • Oak Deck (Screwed down with heavy duty 5/16" screws)
- Adjustable Pintle Hitch • V-shaped Tongue Mount Toolbox
- (2) Dual Speed Semi-Style Landing Gear
- Dual air bag tilting system w/dual air brake chamber locking system
- Solid Front Rail • 4" Jr. I-beam Crossmembers on 14" centers
- 8" Channel Side Rail • 1/4" Steel Over the Wheels
- D-rings—Every 4' On Side Rail • (2) 1/2" Grade 70 Transporter Safety Chains
- Rubber Mounted LED Lights • Mud Flaps • Reflector Tape
- Zinc Rich Primed and Powder Coated