



IN A WORLD OF TRAILERS,
TRAVIS LEADS.

VERTEX[®]

**30 YEARS,
OVER 15,000 TRAILERS**



FRAMELESS

THE VERTEX[™]

ver•tex a patented trailer design which combines **Vert**ical panels of an **Ex**truded, dual-wall trailer. Also, the highest point, the apex, or summit.

In production since April of 2009, the VERTEX[™] continues to add to the powerful line-up of smooth-sided innovations from Travis that date back to 1989.



FRAME-TYPE



QUARTER-FRAME OR HIGH-SPILL

The patented VERTEX[™] boasts many features and benefits:

- Available as a Frameless, Frame-type, or Quarter-Frame,
- Tandem, tri-axle, quad-axle, spread-axle, virtually any configuration
- Also available as Live Floor, or Tipper Trailer
- Lightweight, heavy duty all aluminum construction
- Aerodynamic smooth-sided fuel saving design
- Dual-wall, longer life, extruded 6061-T6 aluminum walls
- Thin wall adds capacity, and inner wall hides any dents
- Polished sides for cosmetic look, and company image
- The VERTEX[™] end dump comes with a Travis 5-year limited warranty



STANDARD SPECIFICATIONS

BODY: Lengths 22' – 40'

ALUMINUM EXTRUSIONS: 6061 T-6

- Dual wall sides, hollow core with internal stiffeners, solid welded, inside and out
- 7" x 4.5" top rail with shedder on top edge
- Fully boxed, 4" x 6" lower rail, with integral side to floor connection
- Cross-members: Patented SST shape, 7" wide top, x 5.5" deep, bucket shaped, that make contact with floor every 7", solid welded to lower rail
- Front & Rear Posts 9" x 4"
- Subframe 13" deep, extruded I-beam
- Heavy-duty crossmembers under dog house

ALUMINUM SHEET: 5454 ALLOY ALUMINUM

- 1/4" (.250) Nose 5454-H32
- 1/4" (.250) floor and hoist box 5454-H34

UNDERBODY

- T-1 Steel rocking, upper coupler, 2" kingpin
- Wide Set Draft Arms with Drop Legs
- Aluminum I-beam subframe
- INTRAAX air ride suspension
- 25,000 lb. capacity, wide track axles with common inner/outer bearings
- Wabco 4S/2M ABS
- Outboard Drums, 10 stud cast hubs
- Radial tires and steel disc wheels
- 8" 5-stage, single acting hydraulic cylinder
- Tire carrier (some exceptions)

TAILGATE

- Perimeter braced 4" x 5" x 1/4" tube
- Rubber sealed with integral connection between extruded rubber and channel in rear post
- Overslung top hinge with grease fitting
- Over center, air-operated and adjustable

OTHER

- 1/2" thick, heavy duty anti-spray, solid rubber flaps
- Sealed wiring harness
- Sealed beam lights
- D.O.T. approved conspicuity tape
- Black enamel paint on steel parts



AVAILABLE OPTIONS:

- Various body widths & side heights to match your application
- Insulation in side panels
- Thicker panels for high wear
- Travis' unique ground-operated barn door and grain door
- Custom lights / paint
- Tarps, from several major manufacturers
- Aluminum draft arms, load bearing drop legs or 2-speed landing gear
- Lightweight hubs and drums
- Aluminum wheels and wide-base tires and wheels
- Many other options are available, including your custom designed items



For more questions or to
find a dealer near you:

Visit our website at
www.travistrailers.com

Or Call us at
(800) 535-4372

www.travistrailers.com
info@travistrailers.com

